Product Specification







USB Charger C 100W with LED Indicator paired with closed blanking plate

The USB Charger C 100W is only applicable for the products below:

	M2	М3	M4	M5
NETBOX M		•	٠	•
NETBOX MEB		•	٠	
NETBOX Profilebox		•	•	•
NETBOX Leaf		•	•	•
NETBOX Smart		•	•	•
NETBOX Line	٠	٠	•	•
NETBOX Style	٠	•	•	•
NETBOX Axial/Axial Comfort	٠	•	•	•
NETBOX Turn/Turn Comfort	•	•	•	•

A. & H. Meyer GmbH Leuchten und Büroelektrik

Fermke 8 32694 Dörentrup Germany

T: +49 5265 9488 0 F: +49 5265 9488 11 www.ah-meyer.de

A. & H. Meyer Sdn Bhd (528797-M)

No. 3, Jalan Astaka U8/84 Section U8, Bukit Jelutong 40150 Shah Alam, Selangor Malaysia

T: +603 7845 7277 F: +603 7845 2155 sales@ah-meyer.com.my

🖳 USB Charger C 100W

Product Description

USB Charger C 100W comes with an LED indicator and a smart communication chip. The intelligent USB Charger C 100W is able to detect how much power delivery is needed for your device. This unit allows your device to be charged with a total maximum current of 5A delivering up to 100W. It comes with a 3 years warranty against manufacturing defects. (T&C Apply)

1 x Type C - 100W USB PD 3.0

Electrical Specifications

USB Charging Sockets: Charging Output:

AC Voltage Range: AC Input Current:

Power Consumption: USB Output Voltage: LED Indicator: Standby Power Consumption: Over Current Protection: Short Circuit Protection: Operating Temperature Range: Maximum Relative Humidity: 5V / 5A (Fixed supply) 9V / 5A (Fixed supply) 12V / 5A (Fixed supply) 15V / 5A (Fixed supply) 20V / 5A (Fixed supply) 3.3V - 21V / 5A 90 - 265V AC 50/60Hz Maximum 2.1A at full load Less than 1mA at idle Maximum 100 watt 3.3V to 21V Blue colour LED indicates power on Less than 0.5 watt Yes Yes 0° to 45° Celsius 85% RH

IN BUSINESS ALL THINGS ARE CONNECTED